



# **ELIMINATOR**

## **NATURAL GAS & LIQUID PROPANE**



### **Stationary Design**

- **Ideal for permanent in-plant installation and operation**
- **LP or NG Fuel Systems**
- **Rugged Baldor® Motors**

### **Reliable General Pumps™!**

- **2000 PSI @ 4.0 GPM**
- **3000 PSI @ 4.0 GPM**
- **3000 PSI @ 5.0 GPM**

---

## **Belt Drive Motor-Pump System!**



# ELIMINATOR

## NATURAL GAS & LIQUID PROPANE

| Part # | HP / VAC / Phase   | Amp Draw | Pump   | Fuel | PSI  | GPM | BTU / Hr | Weight   | Dimensions      |
|--------|--------------------|----------|--------|------|------|-----|----------|----------|-----------------|
| 60331  | 5 / 230 / 1        | 28       | TS1811 | NG   | 2000 | 4.0 | 440,000  | 725 lbs. | 50" x 26" x 50" |
| 60332  | 5 / 230 / 1        | 25       | TS1811 | LP   | 2000 | 4.0 | 440,000  | 725 lbs. | 50" x 26" x 50" |
| 60333  | 7.5 / 230 / 1      | 36       | TS1811 | NG   | 3000 | 4.0 | 440,000  | 725 lbs. | 50" x 26" x 50" |
| 60334  | 7.5 / 230 / 1      | 36       | TS1811 | LP   | 3000 | 4.0 | 440,000  | 725 lbs. | 50" x 26" x 50" |
| 60335  | 10 / 230 - 460 / 3 | 30 - 14  | TS1021 | NG   | 3000 | 5.0 | 440,000  | 725 lbs. | 50" x 26" x 50" |
| 60336  | 10 / 230 - 460 / 3 | 30 - 14  | TS1021 | LP   | 3000 | 5.0 | 440,000  | 725 lbs. | 50" x 26" x 50" |

## Key Features

### The Control Panel

- **Centralized location for all controls.**
- **Hour meter standard on all models.**
- **24V Electrical controls.**
- **Hinged Control Panel allows easy access to electronics & wiring.**

### The Pump and the Motor

- **General Pumps™ brand Industrial Triplex Pumps.**
- **Rugged Baldor® Motors.**
- **Dual Belt Drive System provides redundant power to the pump.**
- **Automatic System Shutdown after 4.5 minutes of inactivity.**
- **Downstream Chemical Injection.**

### The Hot Water System

- **Clean burning, fuel efficient vertical combustion chamber.**
- **Full 140° F heat rise, up to a high limit of 230° F.**
- **NG or LP models available.**
- **Electronic Ignition**
- **Adjustable Auto-Stop Timer.**
- **Thermostat Control System.**
- **5 year warranty on Burner Coil.**

### The Frame and Accessories

- **Protective shroud covers the belts and pulleys from area debris.**
- **Motor and pump system are easily accessible for service or repair.**
- **Includes 50' of 3/8" high pressure hose rated for hot water use, trigger gun, wand, and four QC Nozzles.**

### Factory Installed Options

- **Hose Reel**
- **Remote Control (Wire loop not provided)**
- **Steam Option available**
- **10-inch Draft Diverter**
- **L.P. Burner Available**
- **Built-in downstream (high pressure) detergent injector with detergent & chemical pickup hose and chemical metering valve.**

Your DELCO Distributor is:

