

EQUALIZER SERIES – HOT WATER

INDUSTRIAL

The Equalizer series, offered in both gas and electric models, is designed to accommodate a diverse range of cleaning applications. This comprehensive vertical coil pressure washing system boasts a broad four-wheel stance, enhancing both mobility and versatility, making it a standout choice for your cleaning needs.

UNIT INCLUDES

- Hose
- Trigger gun
- Lance
- Nozzles: 15°, 25°, and 40°
- Chemical injector (65369, 65370)

LIMITED WARRANTY

All Units 10yr Frame, 5yr Pump, 3yr Engine, 1yr Motor

FEATURES

- 1750 RPM slow speed
- NEMA 4X electrical enclosure with rocker switch, hour meter and soap control switch
- External diesel fuel tank (4.4 gal.)
- 120V burner system
- 35' GFCI electrical cord
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 vertical coil

OPTIONAL ACCESSORY

(sold separately and available upon order)

PART #	DESCRIPTION
7112623	Chemical injector kit (gas models)



MODEL #	PART #	PRESSURE	FLOW	ENGINE/MOTOR	PUMP DRIVE	PRODUCT WEIGHT
DEZ2040041B ¹	65369	2000 PSI	4.0 GPM	5HP 230V 1Ø 23A	UDOR Belt	550 lbs.
DEZ2040042B ¹	65370	2000 PSI	4.0 GPM	5HP 230V 1Ø 23A	UDOR Direct	550 lbs.
DEZ3040252EDC1 ¹	65069	3000 PSI	4.0 GPM	HONDA® GX390* w/Recoil Key-start	General Pump Direct	525 lbs.
DEZ3040242EDC1 ¹	65373	3000 PSI	4.0 GPM	HONDA® GX390* w/Recoil Key-start	UDOR Direct	525 lbs.
DEZ4040142EDC1 ¹	65374	4000 PSI	4.0 GPM	CRX420* w/Key-start	UDOR Direct	525 lbs.

PUMPS

General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- 13" premium heavy-duty tires for easy mobility and vibration dampening

HOSE

- 3/8" x 50' steel-braided Armor Hose®

NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT	FUEL TANK CAPACITY
CRX® 420	420cc	1.6 gal
HONDA® GX390	389cc	1.6 gal

DIMENSIONS

All Units L 35" x W 30" x H 43"

¹ - This product is 49-State/EPA-Compliant. Not for sale in the state of California.

* - Indicates engine is equipped with low-oil shutdown technology. Refer to page 34 for additional information.