



ELIMINATOR SERIES

An industrial enclosed cabinet that is designed to be easily serviced. This stationary hot water pressure washer is equipped with a natural gas or LP burner system. A 24V operating system with time delay shut off is standard on all models.

MODEL SPECIFICATIONS

MODEL SHOWN: 65030

FEATURES

- NEMA 4X electrical enclosure with rocker switch, thermostat control, hour meter and soap control switch
- 1/2" Schedule 80 coil
- Soap solenoid with metering valve
- Roll down doors with lock & key plus slide out tray for easy servicing
- Time delay shut down
- Remote box ready wired
- Float tank

FRAME

- Heavy-duty, powder coated welded steel frame
- Corrosion resistant, stainless steel vented panels

PUMP

- Belt drive configuration
- Axialign™ Adjustment System allows for easy belt adjustment and maintenance to be accomplished with a single bolt adjustment
- Oversized bypass hose



INCLUDED ACCESSORIES

- Heat-resistant spray gun (up to 320° F)
- 48" Steel lance with insulated grip and 1/4" QC fitting
- 3/8" x 50' Steel-braided Armor Hose™
- High quality QC nozzles: 15°, 25°, 40°



*Optional Accessories (sold separately and available upon order)

- 7110238 - Draft diverter
- 7110785 - Auto start/stop shut off
- 7109483 - Wired NEMA 4X remote operating station

DIMENSIONS

| | |
|--------|-----|
| Depth | 30" |
| Width | 50" |
| Height | 53" |



ELIMINATOR SERIES

| MODEL # | PUMP | MOTOR | FUEL TYPE | PSI | GPM | PRODUCT WEIGHT |
|---------|-------|----------|----------------|------|-----|----------------|
| 65030 | COMET | 230V, 1Ø | Natural Gas | 2000 | 4.0 | 807 lbs |
| 65031 | COMET | 230V, 3Ø | Natural Gas | 2000 | 4.0 | 844 lbs |
| 65032 | COMET | 460V, 3Ø | Natural Gas | 2000 | 4.0 | 806 lbs |
| 65033 | COMET | 230V, 1Ø | Liquid Propane | 2000 | 4.0 | 800 lbs |
| 65034 | COMET | 230V, 3Ø | Liquid Propane | 2000 | 4.0 | 813 lbs |
| 65035 | COMET | 460V, 3Ø | Liquid Propane | 2000 | 4.0 | 806 lbs |
| 65036 | COMET | 230V, 1Ø | Natural Gas | 3000 | 4.0 | 834 lbs |
| 65037 | COMET | 230V, 3Ø | Natural Gas | 3000 | 4.0 | 794 lbs |
| 65038 | COMET | 460V, 3Ø | Natural Gas | 3000 | 4.0 | 804 lbs |
| 65039 | COMET | 230V, 1Ø | Liquid Propane | 3000 | 4.0 | 854 lbs |
| 65040 | COMET | 230V, 3Ø | Liquid Propane | 3000 | 4.0 | 820 lbs |
| 65041 | COMET | 460V, 3Ø | Liquid Propane | 3000 | 4.0 | 806 lbs |
| 65042 | COMET | 230V, 1Ø | Natural Gas | 3000 | 5.0 | 839 lbs |
| 65043 | COMET | 230V, 3Ø | Natural Gas | 3000 | 5.0 | 800 lbs |
| 65044 | COMET | 460V, 3Ø | Natural Gas | 3000 | 5.0 | 810 lbs |
| 65045 | COMET | 230V, 1Ø | Liquid Propane | 3000 | 5.0 | 820 lbs |
| 65046 | COMET | 230V, 3Ø | Liquid Propane | 3000 | 5.0 | 800 lbs |
| 65047 | COMET | 460V, 3Ø | Liquid Propane | 3000 | 5.0 | 816 lbs |
| 65048 | COMET | 230V, 3Ø | Natural Gas | 3000 | 8.0 | 800 lbs |
| 65049 | COMET | 460V, 3Ø | Natural Gas | 3000 | 8.0 | 760 lbs |
| 65050 | COMET | 230V, 3Ø | Liquid Propane | 3000 | 8.0 | 814 lbs |
| 65051 | COMET | 460V, 3Ø | Liquid Propane | 3000 | 8.0 | 820 lbs |