

MOBILE TRAILER SERIES – HOT WATER

INDUSTRIAL

The Delco® Mobile Trailer series represents self-sufficient cleaning powerhouses. These portable Mobile Trailers are ingeniously engineered to harness the power of Delco machines, providing effective cleaning solutions even in locations where water supply is scarce. This makes them an ideal choice for job sites with limited resources.

UNIT INCLUDES

- Hose
- Nozzles 15°, 25°, 40°, and soap
- Lance
- Downstream injector
- Trigger gun

LIMITED WARRANTY

ALL UNITS 10yr Frame, 5yr Pump, 3yr Engine

FEATURES

- 1750 RPM slow speed
- 1 – 200' high-pressure hose reel with 100' high-pressure hose
- 1 – 200' supply hose reel with 90' supply hose
- Translucent polyethylene water supply tank with easy-to-read water level indicators
- Jack with swivel wheel for easy maneuvering
- 3500 lb. axle with leaf-spring suspension for a smooth ride
- Electric brake system
- Burner fuels: No. 1/No. 2 diesel or kerosene



95101



POWERED BY HONDA



MODEL #	PART#	PRESSURE	FLOW	ENGINE	PUMP	AXLE RATING	WATER TANK SIZE	TIRE	PRODUCT WEIGHT
DTRS23555331E ¹	95100	3500 PSI	5.5 GPM	VANGUARD® 570cc*	COMET	3500 lbs. Rated (x1)	225 gal. with Steel Straps and Drain Petcock	14" w/6-ply	1500 lbs.
DTRS23555251E ¹	95101	3500 PSI	5.5 GPM	HONDA® GX690* w/Recoil & Key-start	General Pump®	3500 lbs. Rated (x1)	225 gal. with Steel Straps and Drain Petcock	14" w/6-ply	1500 lbs.
DTRS33555331E ¹	95107	3500 PSI	5.5 GPM	VANGUARD® 570cc*	COMET	4500 lbs. Rated (x2)	525 gal. with Steel Straps and Drain Petcock	16" w/6-ply	3500 lbs.
DTRS24050251E ¹	95103	4000 PSI	5.0 GPM	HONDA® GX690* w/Recoil & Key-start	General Pump®	3500 lbs. Rated (x1)	225 gal. with Steel Straps and Drain Petcock	14" w/6-ply	1500 lbs.
DTRS24050331E ¹	95104	4000 PSI	5.0 GPM	VANGUARD® 570cc*	COMET	3500 lbs. Rated (x1)	225 gal. with Steel Straps and Drain Petcock	14" w/6-ply	1500 lbs.

PUMPS

General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

COMET Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

HOSES

- 3/8" x 100' steel-braided Armor Hose®

High-Pressure Hose Reel

- Size: 200'

Supply Hose

- Size: 5/8" x 90'

Supply Hose Reel

- Standard - 200'

NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

ADDITIONAL SPECS

Trailer Frame

- Rectangular thick wall steel tubing

Lighting

- LED

Trailer Hitch Ball Size

- 2" ball coupling

ADDITIONAL FEATURES

- Equipped with 48" toolbox
- 95107 equipped with 16 gal. chemical tank

ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
HONDA® GX690	688cc
VANGUARD® 570cc	570cc

DIMENSIONS

95100, 95101, 95103, 95104	L 156" (includes tongue) x W 68" x H 62"
95107	L 192" (includes tongue) x W 90" x H 62"

¹ - This product is 49-State/EPA-Compliant. Not for sale in the state of California.

* - Indicates engine is equipped with low-oil shutdown technology. Refer to page 34 for additional information.