

ELIMINATOR SERIES - HOT WATER

INDUSTRIAL

UNIT INCLUDES

- Hose
- Lance
- Trigger gun
- Nozzles: 15°, 25°, and 40°
- High-pressure soap injector

LIMITED WARRANTY

All Units 10yr Frame, 5yr Pump, 1yr Motor

FEATURES

- 1750 RPM slow speed
- NEMA 4X electrical enclosure with rocker switch, hour meter and soap control switch
- High-pressure soap with metering valve
- Roll-down doors with lock
- Slide out motor pump tray
- Time delay shut-down
- Remote box ready wired
- Float tank
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 vertical coil

OPTIONAL ACCESSORY (sold separately & available upon order)

PART #	DESCRIPTION
7100283	Draft diverter
7110785	Auto start/stop shut-off
7110510	Wired NEMA 4X remote operating station



65030



MODEL #	PART #	PRESSURE	FLOW	MOTOR	BTU	PUMP DRIVE	FUEL TYPE	PRODUCT WEIGHT
DNG2040031B	65030	2000 PSI	4.0 GPM	5HP 230V 1Ø 21A	380,000	UDOR Belt	Natural Gas	807 lbs.
DNG2040031C	65031	2000 PSI	4.0 GPM	5HP 230V 3Ø 12.6A	380,000	UDOR Belt	Natural Gas	844 lbs.
DNG2040031D	65032	2000 PSI	4.0 GPM	5HP 460V 3Ø 6.3A	380,000	UDOR Belt	Natural Gas	806 lbs.
DLP2040031B	65033	2000 PSI	4.0 GPM	5HP 230V 1Ø 21A	450,000	UDOR Belt	Liquid Propane	800 lbs.
DLP2040031C	65034	2000 PSI	4.0 GPM	5HP 230V 3Ø 12.6A	450,000	UDOR Belt	Liquid Propane	813 lbs.
DLP2040031D	65035	2000 PSI	4.0 GPM	5HP 460V 3Ø 6.3A	450,000	UDOR Belt	Liquid Propane	806 lbs.
DNG3040031B	65036	3000 PSI	4.0 GPM	7.5HP 230V 1Ø 36A	380,000	UDOR Belt	Natural Gas	834 lbs.
DNG3040031C	65037	3000 PSI	4.0 GPM	7.5HP 230V 3Ø 19.8A	380,000	UDOR Belt	Natural Gas	794 lbs.
DNG3040031D	65038	3000 PSI	4.0 GPM	7.5HP 460V 3Ø 9.9A	380,000	UDOR Belt	Natural Gas	804 lbs.
DLP3040031B	65039	3000 PSI	4.0 GPM	7.5HP 230V 1Ø 36A	450,000	UDOR Belt	Liquid Propane	854 lbs.
DLP3040031C	65040	3000 PSI	4.0 GPM	7.5HP 230V 3Ø 19.8A	450,000	UDOR Belt	Liquid Propane	820 lbs.
DLP3040031D	65041	3000 PSI	4.0 GPM	7.5HP 460V 3Ø 9.9A	450,000	UDOR Belt	Liquid Propane	806 lbs.
DNG3050031B	65042	3000 PSI	5.0 GPM	10HP 230V 1Ø 39A	380,000	UDOR Belt	Natural Gas	839 lbs.
DNG3050031C	65043	3000 PSI	5.0 GPM	10HP 230V 3Ø 25A	380,000	UDOR Belt	Natural Gas	800 lbs..
DNG3050031D	65044	3000 PSI	5.0 GPM	10HP 460V 3Ø 12.5A	380,000	UDOR Belt	Natural Gas	810 lbs
DLP3050031B	65045	3000 PSI	5.0 GPM	10HP 230V 1Ø 39A	450,000	UDOR Belt	Liquid Propane	820 lbs.
DLP3050031C	65046	3000 PSI	5.0 GPM	10HP 230V 3Ø 25A	450,000	UDOR Belt	Liquid Propane	800 lbs.
DLP3050031D	65047	3000 PSI	5.0 GPM	10HP 460V 3Ø 12.5A	450,000	UDOR Belt	Liquid Propane	816 lbs.
DNG3080031C	65048	3000 PSI	8.0 GPM	15HP 230V 3Ø 35A	380,000	UDOR Belt	Natural Gas	800 lbs.
DNG3080031D	65049	3000 PSI	8.0 GPM	15HP 460V 3Ø 17.5A	380,000	UDOR Belt	Natural Gas	760 lbs.
DLP3080031C	65050	3000 PSI	8.0 GPM	15HP 230V 3Ø 35A	450,000	UDOR Belt	Liquid Propane	814 lbs.
DLP3080031D	65051	3000 PSI	8.0 GPM	15HP 460V 3Ø 17.5A	450,000	UDOR Belt	Liquid Propane	820 lbs.

PUMPS

UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

FRAME

- Powder-coated for corrosion resistance
- Corrosion resistant, stainless steel vented panels
- Wall-mount

HOSE

- 3/8" x 50' steel-braided Armor Hose®

DIMENSIONS

65030, 65031, 65032, 65033, 65034, 65035, 65036, 65037, 65038, 65039, 65040, 65041, 65042, 65043, 65044, 65045, 65046, 65047, 65048, 65049, 65050, 65051

L 30" x W 50" x H 53"

ELIMINATOR SERIES - HOT WATER (CONT.)

INDUSTRIAL

AVAILABLE Q2 2025

UNIT INCLUDES

- Hose
- Lance
- Trigger gun
- Nozzles: 15°, 25°, and 40°
- High-pressure soap injector

LIMITED WARRANTY

All Units 10yr Frame, 5yr Pump, 1yr Motor

FEATURES

- 1750 RPM slow speed
- NEMA 4X electrical enclosure with rocker switch, hour meter and soap control switch
- High-pressure soap with metering valve
- Roll-down doors with lock
- Slide out motor pump tray
- Time delay shut-down
- Remote box ready wired
- Float tank
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 vertical coil

OPTIONAL ACCESSORY (sold separately & available upon order)

PART #	DESCRIPTION
7100283	Draft diverter
7110785	Auto start/stop shut-off
7110510	Wired NEMA 4X remote operating station



65184



MODEL #	PART #	PRESSURE	FLOW	MOTOR	BTU	PUMP DRIVE	FUEL TYPE	PRODUCT WEIGHT
ELM3040041BNG	65184	3000 PSI	4.0 GPM	7.5HP 230V 1Ø 32A	380,000	UDOR Belt	Natural Gas	860 lbs.
ELM3050041CNG	65190	3000 PSI	5.0 GPM	10HP 230V 3Ø 30A	380,000	UDOR Belt	Natural Gas	860 lbs.
ELM3050041DNG	65191	3000 PSI	5.0 GPM	10HP 460V 3Ø 15A	380,000	UDOR Belt	Natural Gas	860 lbs.
ELM3080041CNG	65246	3000 PSI	8.0 GPM	15HP 230V 3Ø 42A	750,000	UDOR Belt	Natural Gas	1660 lbs.
ELM3080041DNG	65247	3000 PSI	8.0 GPM	15HP 460V 3Ø 21A	750,000	UDOR Belt	Natural Gas	1660 lbs.
ELM3080041DLP	65286	3000 PSI	8.0 GPM	15HP 460V 3Ø 21A	760,000	UDOR Belt	Liquid Propane	1660 lbs.
ELM3010041DNG	65283	3000 PSI	10.0 GPM	20HP 460V 3Ø 28A	750,000	UDOR Belt	Natural Gas	1660 lbs.

PUMPS

UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

FRAME

- Powder-coated for corrosion resistance
- Corrosion resistant, stainless steel vented panels
- Wall-mount

HOSE

- 3/8" x 50' steel-braided Armor Hose®

DIMENSIONS

65184, 65190, 65191	L 52" x W 36" x H 51"
65246, 65247, 65286, 65283	L 64" x W 36" x H 61"