

# EQUALIZER SERIES - HOT WATER

INDUSTRIAL

The Equalizer series, offered in both gas and electric models, is designed to accommodate a diverse range of cleaning applications. This comprehensive vertical coil pressure washing system boasts a broad four-wheel stance, enhancing both mobility and versatility, making it a standout choice for your cleaning needs.

## UNIT INCLUDES

- Hose
- Spray gun
- Lance
- Nozzles: 15°, 25°, 40°
- Adjustable soap control (electric models)

## LIMITED WARRANTY

All Units 10yr Frame, 5yr Pump, 3yr Engine, 1yr Motor

## FEATURES

- 1750 RPM slow speed
- NEMA 4X electrical enclosure with rocker switch, hour meter and soap control switch
- External diesel fuel tank (4.4 gal.)
- 120V burner system
- 35' GFCI electrical cord
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 vertical coil

## OPTIONAL ACCESSORY

(sold separately and available upon order)

PART #	DESCRIPTION
7112623	Chemical Injector Kit (gas models)



65068



MODEL #	PART #	DESCRIPTION	PRESSURE	FLOW	ENGINE/MOTOR	PUMP	DRIVE	PRODUCT WEIGHT
DEZ1030032A	65060	EQUALIZER 1030	1000 PSI	3.0 GPM	2HP   120V   1Ø   21A	COMET	Direct	519 lbs.
DEZ1030032B	65061	EQUALIZER 1030	1000 PSI	3.0 GPM	2HP   230V   1Ø   10.5A	COMET	Direct	549 lbs.
DEZ2040032B	65062	EQUALIZER 2040	2000 PSI	4.0 GPM	5HP   230V   1Ø   21A	COMET	Direct	566 lbs.
DEZ2040031B	65063	EQUALIZER 2040	2000 PSI	4.0 GPM	5HP   230V   1Ø   21A	COMET	Belt	526 lbs.
DEZ3040031C	65064	EQUALIZER 2040	3000 PSI	4.0 GPM	5HP   230V   3Ø   12.6A	COMET	Belt	526 lbs.
DEZ3040232E <sup>1</sup>	65068	EQUALIZER 3040HC	3000 PSI	4.0 GPM	HONDA® GX390*	COMET	Direct	525 lbs.
DEZ3040252E <sup>1</sup>	65069	EQUALIZER 3040HG	3000 PSI	4.0 GPM	HONDA® GX390*	General Pump®	Direct	514 lbs.
DEZ4040132E <sup>1</sup>	65147	EQUALIZER 3040C	4000 PSI	4.0 GPM	CRX®420* w/Key-Start	COMET	Direct	525 lbs.

## PUMPS

### General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass head
- Heat-resistant ceramic plunger sleeves
- External unloader with bypass hose

### COMET Industrial Triplex Pump

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass head
- Heat-resistant ceramic plunger sleeves
- External unloader with bypass hose

## FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- 13" premium heavy-duty tires for easy mobility and vibration dampening

## HOSE

- 3/8" x 50' steel-braided Armor Hose™

## ENGINES

ENGINE	DISPLACEMENT	FUEL TANK CAPACITY
CRX® 420	420cc	2.0 gal
HONDA® GX390	389cc	2.0 gal

## DIMENSIONS

All Units L 35" x W 30" x H 43"

<sup>1</sup> - This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* - Indicates engine is equipped with low oil shutdown technology. Refer to page 32 for additional information.