



# INDUSTRIAL EQUIPMENT CATALOG

**CRX**®



# DUAL WASH PRO SERIES

PATENT PENDING

## COLD WATER

Effortlessly transition between soft washing and pressure washing with a plug-and-play design—no wires, batteries, or electronics needed. Built with chemical-resistant seals and stainless-steel fittings, it offers exceptional durability and corrosion resistance. Streamline your workflow by replacing multiple machines with one versatile solution, delivering optimal cleaning performance while saving water.

### LIMITED WARRANTY

- All Units**
- 10-Year Baseplate
  - 5-Year Pump
  - Lifetime Pump Manifold
  - 3-Year Commercial HONDA® Engine
  - 3-Year CRX® Engine

### FEATURES

- Comet TW-D triplex pump with a stainless steel or nickel-plated manifold and long-life, chemical-resistant HP seals (including SH)
- Stainless-steel fittings and couplers
- Stainless-steel heavy-duty 3-way ball valve for simple cleaning-mode control
- 2:1 gearbox
- Welded anodized aluminum base plate
- Always full flow
- Plug-n-play hookup
- Pressure relief valve
- Thermal relief valve
- Soft wash bypass for remote tank applications

65434



**CRX** POWERED by **HONDA**

MODEL #	PART #	HP PRESSURE	SW PRESSURE	FLOW HP/SW	ENGINE	PUMP / DRIVE	MANIFOLD
DWP3080133ESSM <sup>1</sup>	65434	3000 PSI	300 PSI	8 GPM	CRX® 680* / Key-start	COMET, TW-D / Gear	Stainless Steel
DWP3080133ENPM <sup>1</sup>	65438	3000 PSI	300 PSI	8 GPM	CRX® 680* / Key-start	COMET, TW-D / Gear	Nickel-plated Brass
DWP3080233ESSM <sup>1</sup>	65437	3000 PSI	300 PSI	8 GPM	HONDA® iGX700* Key-start	COMET, TW-D / Gear	Stainless Steel
DWP3080233ENPM <sup>1</sup>	65441	3000 PSI	300 PSI	8 GPM	HONDA® iGX700* Key-start	COMET, TW-D / Gear	Nickel-plated Brass
DWP3010133ESSM <sup>1</sup>	65436	3000 PSI	300 PSI	10 GPM	CRX® 750* / Key-start	COMET, TW-D / Gear	Stainless Steel
DWP3010133ENPM <sup>1</sup>	65440	3000 PSI	300 PSI	10 GPM	CRX® 750* / Key-start	COMET, TW-D / Gear	Nickel-plated Brass
DWP4080133ESSM <sup>1</sup>	65435	4000 PSI	300 PSI	8 GPM	CRX® 750* / Key-start	COMET, TW-D / Gear	Stainless Steel
DWP4080133ENPM <sup>1</sup>	65439	4000 PSI	300 PSI	8 GPM	CRX® 750* / Key-start	COMET, TW-D / Gear	Nickel-plated Brass

### OPTIONAL ACCESSORIES

(sold separately and available upon order)

PART #	DESCRIPTION
80629	Wash Down Gun (8-9 GPM)
80667	Wash Down Gun (10-12 GPM)
80630	50' Soft Wash Hose
80631	100' Soft Wash Hose
80632	200' Soft Wash Hose
80634	8.0 GMP Chemical Injector Kit
80635	10.0 GPM Chemical Injector Kit
80633	Stainless-steel Quick Coupler Kit (Includes socket and plug connections)

### BASEPLATE

#### Aircraft-Grade Aluminum Frame

- Light weight and corrosion-resistant
- Forklift slots
- Rubber vibration dampers

### ENGINE LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
CRX® 680	679cc
CRX® 750	750cc
HONDA® iGX700	688cc

### DIMENSIONS & WEIGHTS

All units L 41" x W 27" x H 23" | 254 lbs.

<sup>1</sup> This product is 49-State/EPA-Compliant. Not for sale in the state of California.  
\* Indicates engine is equipped with low-oil shutdown technology.

For more information on how to order, please contact your sales representative.

# PATRIOT SERIES

## HOT WATER

The Patriot, designed for versatility, offers both portability and stationary use. It is engineered to deliver a superior clean tailored to your needs. The units are equipped with extended fuel tanks.

### UNIT INCLUDES

- Hose
- Lance
- Trigger Gun
- Nozzles: 15°, 25°, and 40°
- Engine Oil 10W-30

### LIMITED WARRANTY

All Units 10-Year Frame, 5-Year Pump, 3-Year Engine

### FEATURES

- 120V burner system
- 1750 RPM slow speed
- V-twin horizontal engine with key-start (battery not included)
- NEMA 4X electrical enclosure with burner on/off rocker switch and hour meter
- Corrosion-resistant stainless steel coil cover
- Isolated pump & engine plate with vibration dampeners
- 3.4 kw generator with one 120V duplex outlet
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 horizontal coil



65013

### OPTIONAL ACCESSORIES (sold separately & available upon order)

PART #	DESCRIPTION
80657	Analog Thermostat Kit
80664	Steam Kit



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP / DRIVE	GAS TANK CAPACITY	DIESEL TANK CAPACITY	PRODUCT WEIGHT
DPT3080251EAC1 <sup>†</sup>	65013	3000 PSI	8.0 GPM	HONDA® GX690* Key-start	General Pump® / Belt	15 gal.	15 gal.	1050 lbs.
DPT3080151EAC1 <sup>†</sup>	65148	3000 PSI	8.0 GPM	CRX® 750* Key-start	General Pump® / Belt	15 gal.	15 gal.	1050 lbs.
DPT3080241EAC1 <sup>†</sup>	65366	3000 PSI	8.0 GPM	HONDA® GX690* Key-start	UDOR® / Belt	15 gal.	15 gal.	1050 lbs.
DPT3080141EAC1 <sup>†</sup>	65367	3000 PSI	8.0 GPM	CRX® 750* Key-start	UDOR® / Belt	15 gal.	15 gal.	1050 lbs.

### PUMPS

#### General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

#### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options

### HOSE

- 3/8" x 50' steel-braided Armor Hose®

### NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

### ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
CRX® 750	750cc
HONDA® GX690	688cc

### DIMENSIONS

All Units L 47" x W 43" x H 39"

<sup>†</sup> This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* Indicates engine is equipped with low-oil shutdown technology.

# COBALT SERIES

## HOT WATER

Take on the toughest cleaning jobs with the Cobalt series. Built with a robust twin-cylinder engine, it delivers dependable power that gets the job done. When turned on the diesel-fired heating system provides up to 120°F heat rise, helping tackle even the toughest tasks with ease.

### UNIT INCLUDES

- Hose
- Lance
- Trigger Gun
- Nozzles: 15°, 25°, 40°, and Soap
- Engine Oil 10W-30
- Downstream Injector

### LIMITED WARRANTY

**ALL UNITS** 10-Year Frame, 5-Year Pump, 3-Year Engine

### FEATURES

- 1750 RPM slow speed
- V-twin horizontal engine with key-start (battery not included)
- NEMA 4X electrical enclosure with burner on/off rocker switch and hour meter
- Corrosion-resistant stainless-steel coil cover
- Isolated pump & engine plate with vibration dampeners
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 horizontal coil

### OPTIONAL ACCESSORIES (sold separately & available upon order)

PART #	DESCRIPTION
80657	Analog Thermostat Kit
80664	Steam Kit



65002



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP / DRIVE	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
DCT3555251EDC1 <sup>1</sup>	65002	3500 PSI	5.5 GPM	HONDA® GX690* Key-start	General Pump® / Belt	7.5 gal.	7.5 gal.	650 lbs.
DCT3555151EDC1 <sup>1</sup>	65144	3500 PSI	5.5 GPM	CRX® 680* / Key-start	General Pump® / Belt	7.5 gal.	7.5 gal.	650 lbs.
DCT3555241EDC1 <sup>1</sup>	65298	3500 PSI	5.5 GPM	HONDA® GX690* Key-start	UDOR® / Belt	7.5 gal.	7.5 gal.	650 lbs.
DCT3555141EDC1 <sup>1</sup>	65351	3500 PSI	5.5 GPM	CRX® 680* / Key-start	UDOR® / Belt	7.5 gal.	7.5 gal.	650 lbs.
DCT4050151EDC1 <sup>1</sup>	65158	4000 PSI	5.0 GPM	CRX® 680* / Key-start	General Pump® / Belt	7.5 gal.	7.5 gal.	650 lbs.
DCT4050241EDC1 <sup>1</sup>	65299	4000 PSI	5.0 GPM	HONDA® GX690* Key-start	UDOR® / Belt	7.5 gal.	7.5 gal.	650 lbs.
DCT4050141EDC1 <sup>1</sup>	65352	4000 PSI	5.0 GPM	CRX® 680* / Key-start	UDOR® / Belt	7.5 gal.	7.5 gal.	650 lbs.

### PUMPS

#### General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

#### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options

### HOSE

- 3/8" x 50' steel-braided Armor Hose®

### NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

### ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
CRX® 680	679cc
HONDA® GX690	688cc

### DIMENSIONS

**All Units** L 46" x W 42" x H 37"

<sup>1</sup> This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* Indicates engine is equipped with low-oil shutdown technology.

# VERSA SERIES

## HOT WATER

The Versa series, available in either powder-coated or stainless steel frames, stands as a dependable option for a wide range of cleaning equipment needs. Its superior quality and unique design set this horizontal coil electric cleaning system apart, making it the best in its class.

### UNIT INCLUDES

- Hose
- Lance
- Trigger Gun
- Nozzles: 15°, 25°, and 40°
- Upstream Low-Pressure Soap Injector

### LIMITED WARRANTY

All Units 10-Year Frame, 5-Year Pump, 1-Year Motor

### FEATURES

- 1750 RPM slow speed
- NEMA 4X electrical enclosure with burner on/off rocker switch, and hour meter, time delay-shut off
- Large capacity diesel fuel tank
- Horizontal heat exchanger with stainless steel housing
- 120V or 230V burner
- Burner fuels: No. 1/No. 2 diesel or kerosene

### OPTIONAL ACCESSORY

(sold separately and available upon order)

PART #	DESCRIPTION
7110785	Auto Start/Stop Shut Off



65375



MODEL #	PART #	DESCRIPTION	PRESSURE	FLOW	MOTOR	PUMP / DRIVE	DIESEL TANK	PRODUCT WEIGHT
DVST2.525041AAC1	65381	Super Steamer	250 PSI	2.5 GPM	0.75HP / 120V / 1Ø / 8.4A	UDOR® / Belt	6.7 gal.	610 lbs.
DV2040041BAC2	65375	High-Pressure	2000 PSI	4.0 GPM	5HP / 230V / 1Ø / 23A	UDOR® / Belt	6.7 gal.	610 lbs.
DV3040041BAC2	65377	High-Pressure	3000 PSI	4.0 GPM	7.5HP / 230V / 1Ø / 31A	UDOR® / Belt	6.7 gal.	610 lbs.
DV3040041CAC2	65378	High-Pressure	3000 PSI	4.0 GPM	7.5HP / 230V / 3Ø / 19A	UDOR® / Belt	6.7 gal.	610 lbs.

### STAINLESS STEEL

DVSTSS2.525041AAC1	65382	Super Steamer	250 PSI	2.5 GPM	0.75HP / 120V / 1Ø / 8.4A	UDOR® / Belt	6.7 gal.	610 lbs.
DVSS2040041BAC2	65376	High-Pressure	2000 PSI	4.0 GPM	5HP / 230V / 1Ø / 23A	UDOR® / Belt	6.7 gal.	610 lbs.
DVSS3040041BAC2	65379	High-Pressure	3000 PSI	4.0 GPM	7.5HP / 230V / 1Ø / 31A	UDOR® / Belt	6.7 gal.	610 lbs.
DVSS3040041CAC2	65380	High-Pressure	3000 PSI	4.0 GPM	7.5HP / 230V / 3Ø / 19A	UDOR® / Belt	6.7 gal.	610 lbs.

### PUMP

#### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated frame and panels for corrosion resistance (65381, 65375, 65377, 65378)
- Stainless steel frame and panels (65382, 65376, 65379, 65380)

### HOSE

- 3/8" x 50' steel-braided Armor Hose®

### NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

### WHEELS

- 13" Premium pneumatic

### DIMENSIONS

All Units L 35" x W 30" x H 43"

# STREAMLINER SERIES

## HOT WATER

This potent mobile washing system is ingeniously designed to be compact, allowing it to comfortably fit within the confines of a transit van or truck bed, and effortlessly pass through a 36" doorway.

### UNIT INCLUDES

- Hose
- Lance
- Trigger Gun
- Nozzles: 15°, 25°, and 40°
- Engine Oil 10W-30
- Downstream Injector

### LIMITED WARRANTY

**All Units** 10-Year Frame, 5-Year Pump, 3-Year Engine

### FEATURES

- 1750 RPM slow speed
- CRX®, HONDA® key-start engines (battery not included)
- Burner on/off rocker switch and hour meter
- High-temperature safety switch
- Isolated pump and engine plate with vibration dampeners
- 3.4 kW generator with two 120V outlets
- 120V burner system
- Wheel brake system
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" schedule 80 horizontal coil
- Large-capacity fuel tank

### OPTIONAL ACCESSORIES (sold separately & available upon order)

PART #	DESCRIPTION
80657	Analog Thermostat Kit
80646	Steam Kit



65016



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
DSL4040253EDC1 <sup>1</sup>	65016	4000 PSI	4.0 GPM	HONDA® GX390* Key-start	General Pump® / Gear	5.0 gal.	10.0 gal.	450 lbs.
DSL4040242EDC1 <sup>1</sup>	65361	4000 PSI	4.0 GPM	HONDA® GX390* Key-start	UDOR® / Direct	5.0 gal.	10.0 gal.	450 lbs.
DSL4040142EDC1 <sup>1</sup>	65363	4000 PSI	4.0 GPM	CRX® 420* / Key-start	UDOR® / Direct	5.0 gal.	10.0 gal.	450 lbs.
DSL4040143EDC1 <sup>1</sup>	65364	4000 PSI	4.0 GPM	CRX® 420* / Key-start	UDOR® / Gear	5.0 gal.	10.0 gal.	450 lbs.

### PUMPS

#### General Pump® Industrial Triplex

- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

#### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance

### HOSE

- 3/8" x 50' steel-braided Armor Hose®

### NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

### ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
CRX® 420	420cc
HONDA® GX390	389cc

### DIMENSIONS

All Units L 50" x W 32" x H 47"

<sup>1</sup> This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* Indicates engine is equipped with low-oil shutdown technology.

# ELIMINATOR SERIES

## HOT WATER

The Eliminator Series Hot Water Pressure Washer is built for high-demand cleaning environments where reliability, power, and safety are essential. Engineered with a rugged slow-speed system and a fully enclosed, roll-down locking cabinet, the Eliminator delivers professional-grade cleaning performance while protecting internal components from weather, debris, and damage.

Designed for facilities, shops, industrial plants, and commercial operations, this unit combines hot-water efficiency with advanced controls—including time-delay shutdown, soap metering, and remote operation readiness—making it one of the most versatile stationary cleaning systems available.

### UNIT INCLUDES

- Hose
- Lance
- Trigger Gun
- Nozzles: 15°, 25°, and 40°
- High-Pressure Soap Injector

### LIMITED WARRANTY

All Units 10-Year Frame, 5-Year Pump, 1-Year Motor

### FEATURES

- 1750 RPM slow speed
- NEMA 4X electrical enclosure with rocker switch, hour meter and soap control switch
- High-pressure soap with metering valve
- Roll-down doors with lock
- Slide out motor pump tray
- Time delay shut-down
- Remote box ready-wired
- Float tank
- 1/2" schedule 80 vertical coil

### OPTIONAL ACCESSORIES (sold separately & available upon order)

PART #	DESCRIPTION
7100283	Draft Diverter
7110785	Auto Start/Stop Shut-Off
7110510	Wired NEMA 4X Remote Operating Station



65050

**Limited Stock Available**



MODEL #	PART #	PRESSURE	FLOW	MOTOR	BTU	PUMP / DRIVE	FUEL TYPE	PRODUCT WEIGHT
DNG3080031C	65048	3000 PSI	8.0 GPM	15HP / 230V / 3Ø / 35A	380,000	UDOR® / Belt	Natural Gas	800 lbs.
DNG3080031D	65049	3000 PSI	8.0 GPM	15HP / 460V / 3Ø / 17.5A	380,000	UDOR® / Belt	Natural Gas	760 lbs.
DLP3080031C	65050	3000 PSI	8.0 GPM	15HP / 230V / 3Ø / 35A	450,000	UDOR® / Belt	Liquid Propane	814 lbs.
DLP3080031D	65051	3000 PSI	8.0 GPM	15HP / 460V / 3Ø / 17.5A	450,000	UDOR® / Belt	Liquid Propane	820 lbs.

### PUMPS

#### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### FRAME

- Powder-coated for corrosion resistance
- Corrosion-resistant, stainless steel vented panels
- Wall-mount

### HOSE

- 3/8" x 50' steel-braided Armor Hose®

### DIMENSIONS

65048, 65049, 65050, 65051 L 30" x W 50" x H 53"

# ELIMINATOR SERIES CONTINUED

## UNIT INCLUDES

- Hose
- Lance
- Trigger Gun
- Nozzles: 15°, 25°, and 40°
- High-Pressure Soap Injector

## LIMITED WARRANTY

All Units 10-Year Frame, 5-Year Pump, 1-Year Motor

## FEATURES

- 1750 RPM slow speed
- NEMA 4X electrical enclosure with rocker switch, hour meter and soap control switch
- High-pressure soap with metering valve
- Roll-down doors with lock
- Time delay shut-down
- Remote box ready-wired
- Float tank
- 1/2" schedule 80 vertical coil
- Voltage selection (65184 only)  
Choose between 208V or 230V



65184

## OPTIONAL ACCESSORIES (sold separately & available upon order)

PART #	DESCRIPTION
7100283	Draft Diverter
7110785	Auto Start/Stop Shut-Off
80654	Remote Box Kit 24V



MODEL #	PART #	PRESSURE	FLOW	MOTOR	BTU	PUMP / DRIVE	FUEL TYPE	PRODUCT WEIGHT
ELM3040041BNG	65184	3000 PSI	4.0 GPM	7.5HP / 208/230V / 1Ø / 29A	380,000	UDOR® / Belt	Natural Gas	860 lbs.
ELM3050041CNG	65190	3000 PSI	5.0 GPM	10HP / 230V / 3Ø / 25A	380,000	UDOR® / Belt	Natural Gas	860 lbs.
ELM3050041DNG	65191	3000 PSI	5.0 GPM	10HP / 460V / 3Ø / 12.5A	380,000	UDOR® / Belt	Natural Gas	860 lbs.

## ELIMINATOR XL

ELM3080041CNG	65246	3000 PSI	8.0 GPM	15HP / 230V / 3Ø / 36A	750,000	UDOR® / Belt	Natural Gas	1660 lbs.
ELM3080041DNG	65247	3000 PSI	8.0 GPM	15HP / 460V / 3Ø / 18A	750,000	UDOR® / Belt	Natural Gas	1660 lbs.
ELM3080041DLP	65286	3000 PSI	8.0 GPM	15HP / 460V / 3Ø / 18A	760,000	UDOR® / Belt	Liquid Propane	1660 lbs.
ELM3010041DNG	65283	3000 PSI	10.0 GPM	20HP / 460V / 3Ø / 24A	750,000	UDOR® / Belt	Natural Gas	1660 lbs.

## PUMPS

### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

## FRAME

- Powder-coated for corrosion resistance
- Corrosion-resistant, stainless steel vented panels
- Wall-mount

## DIMENSIONS

65184, 65190, 65191	L 52" x W 36" x H 51"
65246, 65247, 65286, 65283	L 64" x W 36" x H 61"

## HOSE

- 3/8" x 50' steel-braided Armor Hose®



Water Inlet/Outlet

NOTE: Movable water inlet/outlet point  
(3 different locations - front, side, or back)

# EQUALIZER SERIES

## HOT WATER

The Equalizer series, offered in both gas and electric models, is designed to accommodate a diverse range of cleaning applications. This comprehensive vertical coil pressure washing system boasts a broad four-wheel stance, enhancing both mobility and versatility, making it a standout choice for your cleaning needs.

### UNIT INCLUDES

- Hose
- Trigger Gun
- Lance
- Nozzles: 15°, 25°, and 40°

### LIMITED WARRANTY

**All Units** 10-Year Frame, 5-Year Pump, 3-Year Engine

### FEATURES

- NEMA 4X electrical enclosure with rocker switch, hour meter and soap control switch
- External diesel fuel tank (4.4 gal.)
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" schedule 80 vertical coil

### OPTIONAL ACCESSORY

(sold separately and available upon order)

PART #	DESCRIPTION
7112623	Chemical Injector Kit



65068



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP / DRIVE	PRODUCT WEIGHT
DEZ3040252EDC1 <sup>1</sup>	65069	3000 PSI	4.0 GPM	HONDA® GX390* Recoil / Key-start	General Pump / Direct	515 lbs.
DEZ3040242EDC1 <sup>1</sup>	65373	3000 PSI	4.0 GPM	HONDA® GX390* Recoil / Key-start	UDOR® / Direct	515 lbs.
DEZ4040142EDC1 <sup>1</sup>	65374	4000 PSI	4.0 GPM	CRX420* / Key-start	UDOR® / Direct	515 lbs.

### PUMPS

#### General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

#### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- 13" premium heavy-duty tires for easy mobility and vibration dampening

### HOSE

- 3/8" x 50' steel-braided Armor Hose®

### NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

### ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT	FUEL TANK CAPACITY
CRX® 420	420cc	1.6 gal
HONDA® GX390	389cc	1.6 gal

### DIMENSIONS

All Units L 35" x W 30" x H 43"

<sup>1</sup> This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* Indicates engine is equipped with low-oil shutdown technology.

# DOMINATOR SERIES

## HOT WATER

The Dominator Series, designed with compactness and user-friendliness in mind, is a testament to high-quality components and remarkable value. This horizontal coil electric hot water pressure washer comes equipped with features like downstream chemical injection, enhancing its functionality and efficiency.

### UNIT INCLUDES

- Hose
- Nozzles: 15°, 25°, 40°, and soap
- Lance
- Downstream Injector
- Trigger Gun

### LIMITED WARRANTY

All Units 10-Year Frame, 5-Year Pump, 1-Year Motor

### FEATURES

- NEMA 4X electrical enclosure with rocker switch and hour meter
- 6.7 gal diesel fuel tank
- Wheel brake system
- 35' GFCI electrical cord
- Burner fuels: No. 1/No. 2 diesel or kerosene



MODEL #	PART #	PRESSURE	FLOW	MOTOR	PUMP	DIESEL TANK	PRODUCT WEIGHT
DDM1030042AAC1	65383	1000 PSI	3.0 GPM	2HP / 120V / 1Ø / 16.4A	UDOR® / Direct	6.7 gal.	410 lbs.
DDM2040042BAC2	65384	2000 PSI	4.0 GPM	5HP / 230V / 1Ø / 23A	UDOR® / Direct	6.7 gal.	410 lbs.

### PUMP

#### UDOR® Industrial Triplex Pump

- 1750 RPM slow speed
- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance

### HOSE

- 3/8" x 50' steel-braided Armor Hose®

### NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

### DIMENSIONS

All Units L 55" x W 31" x H 40"

# CWE SERIES

## COLD WATER

The Delco® CWE Portable Series represents electrically-powered, enclosed cabinet-style cold water washers. Each model is equipped with a belt-drive premium triplex plunger pump, featuring high-temperature seals capable of handling water temperatures up to 165° F. This series combines compact design and user-friendly operation, making it an excellent choice for your cleaning needs.

### UNIT INCLUDES

- Hose
- Lance
- Trigger Gun
- Nozzles: 15°, 25°, 40°, and Soap
- Downstream Injector

### LIMITED WARRANTY

All Units 10-Year Frame, 5-Year Pump, 1-Year Motor

### FEATURES

- High-temperature water feed, capable up to 165° F
- Automatic start/stop feature
- Built-in hour meter
- Belt driven slow speed industrial triplex pump
- Removable handle and wheels
- Wall mount bracket (standard with 65171 only)

### OPTIONAL ACCESSORIES (sold separately & available upon order)

PART #	DESCRIPTION	PART #	DESCRIPTION
80650	Remote Box (Small Frame)	80297	Wall Mount Kit (Small Frame)
80655	Remote Box (Large Frame)	80653	Wall Mount Kit (Large Frame)



65292



65171



MODEL #	PART #	PRESSURE	FLOW	MOTOR	PUMP / DRIVE	FRAME / MATERIAL	PRODUCT WEIGHT
---------	--------	----------	------	-------	--------------	------------------	----------------

### WALL MOUNT

DWM1330042B	65171	1300 PSI	3.0 GPM	3HP / 230V / 1Ø / 13.2A	UDOR® / Direct	Small Wall Mount / Steel	250 lbs.
DWM2040042B	65172	2000 PSI	4.0 GPM	5HP / 230V / 1Ø / 23A	UDOR® / Direct	Small Wall Mount / Steel	250 lbs.
DWM3540041B	65455	3500 PSI	4.0 GPM	10HP / 230V / 1Ø / 38A	UDOR® / Belt	Large Wall Mount / Steel	350 lbs.

### FLOOR MODEL

DFM2040041B	65295	2000 PSI	4.0 GPM	5HP / 230V / 1Ø / 23A	UDOR® / Belt	Large Portable / Steel	350 lbs.
DFM2010031C	65164	2000 PSI	10.0 GPM	15HP / 230V / 3Ø / 35A	COMET / Belt	Large Portable / Steel	350 lbs.
DFM3040041D	65294	3000 PSI	4.0 GPM	7.5HP / 460V / 3Ø / 9.5A	UDOR® / Belt	Large Portable / Steel	350 lbs.
DFMSS3040041D	65296	3000 PSI	4.0 GPM	7.5HP / 460V / 3Ø / 9.5A	UDOR® / Belt	Large Portable / Stainless Steel	350 lbs.
DFM3050041C	65292	3000 PSI	5.0 GPM	10HP / 230V / 3Ø / 25A	UDOR® / Belt	Large Portable / Stainless Steel	350 lbs.
DFMSS3050041C	65293	3000 PSI	5.0 GPM	10HP / 230V / 3Ø / 25A	UDOR® / Belt	Large Portable / Stainless Steel	350 lbs.

### PUMPS

#### COMET Industrial Triplex Pump

- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

#### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### FRAMES

#### Wall Mount

- Powder-coated steel frame for corrosion resistance

#### Portable

- Compact frame for easy storage
- Powder-coated steel frame for corrosion resistance

### HOSE

- 3/8" x 50' steel-braided Armor Hose®

### COVER

- Steel powder-coated panel cover

### NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

### DIMENSIONS

65171, 65172	L 32" x W 16" x H 14"
65455	L 33" x W 22" x H 18"
65164, 65294, 65296, 65292, 65293	L 43" x W 30" x H 39"

# MOBILE TRAILER SERIES

## HOT WATER

The Delco® Mobile Trailer Series delivers powerful hot-water cleaning in a fully mobile platform. Engineered to operate in areas with limited water access, these trailers provide dependable cleaning performance on job sites where resources are scarce.

### UNIT INCLUDES

- Hose
- Lance
- Trigger Gun
- Nozzles 15°, 25°, 40°, and Soap
- Downstream Injector

### LIMITED WARRANTY

**ALL UNITS** 1-Year Trailer Frame, 5-Year Pump, 3-Year Engine

### FEATURES

- 1750 RPM slow speed
- (1) 200' high-pressure hose reel with 100' high-pressure hose
- (1) 200' supply hose reel with 90' supply hose
- Translucent polyethylene water supply tank with easy-to-read water level indicators
- Electric brake system
- Burner fuels: No. 1/No. 2 diesel or kerosene



95101



POWERED by HONDA



MODEL #	PART#	PRESSURE	FLOW	ENGINE	PUMP / DRIVE	AXLE RATING	WATER TANK SIZE	TIRE	BURNER TYPE
---------	-------	----------	------	--------	--------------	-------------	-----------------	------	-------------

### STAGE 2 TRAILERS

DTRS23555251EDC1 <sup>1</sup>	95161	3500 PSI	5.5 GPM	HONDA® GX690* Recoil / Key-start	General Pump® / Belt	3500 lbs. (1)	225 gal.	ST205/75R14	12VDC
DTRS23555141EDC1 <sup>1</sup>	95180	3500 PSI	5.5 GPM	CRX® 680* Recoil / Key-start	UDOR® / Belt	3500 lbs. (1)	225 gal.	ST205/75R14	12VDC
DTRS24050251EDC1 <sup>1</sup>	95163	4000 PSI	5.0 GPM	HONDA® GX690* Recoil / Key-start	General Pump® / Belt	3500 lbs. (1)	225 gal.	ST205/75R14	12VDC

### STAGE 3 TRAILERS

DTRS33080241EAC1 <sup>1</sup>	95177	3000 PSI	8.0 GPM	HONDA® GX690* Recoil / Key-start	UDOR® / Belt	5200 lbs. (2)	525 gal.	ST225/75R15	120VAC
DTRS33080141EAC1 <sup>1</sup>	95181	3000 PSI	8.0 GPM	CRX® 750* Recoil / Key-start	UDOR® / Belt	5200 lbs. (2)	525 gal.	ST225/71R15	120VAC
DTRS33555141EAC1 <sup>1</sup>	95182	3500 PSI	5.5 GPM	CRX® 680* Recoil / Key-start	UDOR® / Belt	5200 lbs. (2)	525 gal.	ST225/75R15	120VAC
DTRS33555251EDC1 <sup>1</sup>	95176	3500 PSI	5.5 GPM	HONDA® GX690* Recoil / Key-start	General Pump® / Belt	5200 lbs. (2)	525 gal.	ST225/71R15	12VDC
DTRS33555241EAC1 <sup>1</sup>	95178	3500 PSI	5.5 GPM	HONDA® GX690* Recoil / Key-start	UDOR® / Belt	5200 lbs. (2)	525 gal.	ST225/75R15	120VAC

### PUMPS

#### General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose to tank

#### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose to tank

### HOSES

- 3/8" x 100' steel-braided Armor Hose®

#### High-Pressure Hose Reel

- Size: 200'

#### Supply Hose

- Size: 5/8" x 90'

#### Supply Hose Reel

- Standard - 200'

### NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

### ADDITIONAL SPECS

**Trailer Frame:** 6" powder coated C-channel

**Lighting:** LED

**Trailer Hitch Ball Size:**

2" ball coupling (Stage 2), 2-5/16" ball coupling (Stage 3)

### ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
HONDA® GX690	688cc

### DIMENSIONS & WEIGHT

95161, 95163, 95180	L 156" (includes tongue) x W 68" x H 62" 1500 lbs.
95176, 95177, 95178, 95181, 95182	L 192" (includes tongue) x W 90" x H 62" 3500 lbs

<sup>1</sup> This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* Indicates engine is equipped with low-oil shutdown technology.



DELCO-CLEANING.COM



SALES@DELCO-CLEANING.COM

**Disclaimer of Liability:** In the preparation of this catalog, every effort has been made to offer the most current, correct, and clearly expressed information possible. Nevertheless, inadvertent errors in information may occur and information may become outdated. In particular, but without limiting anything stated herein, FNA Group, Inc. disclaims any responsibility for errors and accuracy or timeliness of the information that may be contained in this catalog also reserves the right to make changes to its product line at any time without notice. If misleading, or otherwise inaccurate information is brought to our attention, a reasonable effort will be made to fix or remove it. Please contact us at 1-833-362-7368 with any concerns.

**DELCO-CLEANING.COM • SALES@DELCO-CLEANING.COM**