

PATRIOT SERIES - HOT WATER

INDUSTRIAL

The Patriot, designed for versatility, offers both portability and stationary use. It is engineered to deliver a superior clean tailored to your needs. The unit is equipped with a fixed thermostat powered by a dependable 3400W generator.

UNIT INCLUDES

- Hose
- Nozzles: 15°, 25°, 40°
- Lance
- Engine oil 10W-30
- Spray gun

LIMITED WARRANTY

All Units 10yr Frame, 5yr Pump, 3yr Engine

FEATURES

- 1750 RPM slow speed
- V-Twin horizontal engine with key-start (battery not included)
- NEMA 4X electrical enclosure with burner on/off rocker switch and hour meter
- Corrosion resistant stainless steel coil cover
- Isolated pump & engine plate with vibration dampeners
- 3.4 kw generator with one 120V duplex outlet
- 120V burner system
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 horizontal coil



65013



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP	DRIVE	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
DPT3080331E ¹	65011	3000 PSI	8.0 GPM	VANGUARD® 23HP* w/Key-Start	COMET	Belt	15 gal.	15 gal.	855 lbs.
DPT3080251E ¹	65013	3000 PSI	8.0 GPM	HONDA® GX690* w/Key-Start	General Pump®	Belt	15 gal.	15 gal.	896 lbs.
DPT3080131E ¹	65146	3000 PSI	8.0 GPM	CRX® 680* w/Key-Start	COMET	Belt	15 gal.	15 gal.	855 lbs.
DPT3080151E ¹	65148	3000 PSI	8.0 GPM	CRX® 680* w/Key-Start	General Pump®	Belt	15 gal.	15 gal.	896 lbs.

PUMPS

General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass head
- Heat-resistant ceramic plunger sleeves
- External unloader with bypass hose

COMET Industrial Triplex Pump

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass head
- Heat-resistant ceramic plunger sleeves
- External unloader with bypass hose

FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options

HOSE

- 3/8" x 50' steel-braided Armor Hose™

ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT	FUEL TANK
CRX® 680	679cc	External
HONDA® GX690	688cc	External
VANGUARD® 23HP	627cc	External

DIMENSIONS

All Units L 42" x W 45" x H 49"

¹ - This product is 49-State/EPA-Compliant. Not for sale in the state of California.
* - Indicates engine is equipped with low oil shutdown technology. Refer to page 32 for additional information.