

The Cobalt series is equipped with a high-performance pressure washing system driven by a twin cylinder engine, featuring an adjustable thermostat for precision temperature control. Heating of the pressurized water is done effectively with a diesel fired heating system.

MODEL SPECIFICATIONS

FEATURES

- V-Twin horizontal engine with electric start
- NEMA 4X electrical enclosure with burner on/off rocker switch, thermostat control and hour meter
- Corrosion resistant stainless steel coil cover
- 1/2" Schedule 80 coil
- Isolated pump & engine plate with vibration dampeners
- Total fuel capacity of 17.5 gallons (8.75 gallon gas) (8.75 gallon diesel)

FRAME

- Heavy-duty 11/2 round tubular steel design
- Powder coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options

PUMP

- Premium industrial triplex pumps; COMET or GENERAL PUMP®
- Belt drive configuration
- Axialign[™] adjustment system allows for easy belt adjustment and maintenance to be accomplished with a single bolt adjustment
- Oversized by pass hose

INCLUDED ACCESSORIES

- Heat-resistant spray gun (up to 320° F)
- 48" Steel lance with insulated grip and 1/4" QC fitting
- 3/8″ x 50′ Steel-braided Armor Hose™
- High quality QC nozzles: 15°, 25°, 40° and soap
- Downstream detergent injector

*Optional Accessories (sold separately and available upon order)

- 7110781 Water separating fuel filter7110782- Float tank
- **DIESEL TANK MODEL # GAS TANK** PRODUCT ENGINE PUMP PSI **GPM** WEIGHT 65001 VANGUARD[®] 570cc COMET 3500 5.5 8.75 gal 8.75 gal 661 lbs 65002 HONDA® GX630 **GENERAL PUMP®** 3500 5.5 8.75 gal 8.75 gal 666 lbs HONDA® GX630 8.75 gal 65004 **GENERAL PUMP®** 4000 5.0 8.75 gal 613 lbs 65005 VANGUARD[®] 570cc COMET 4000 5.0 8.75 gal 613 lbs 8.75 gal





DIMENSIONS	
Depth	42″
Width	46″
Height	38″

