

# STREAMLINER SERIES - HOT WATER

INDUSTRIAL

This potent mobile washing system is ingeniously designed to be compact, allowing it to comfortably fit within the confines of a transit van or truck bed, and effortlessly pass through a 36" doorway.

## UNIT INCLUDES

- Hose
- Lance
- Spray gun
- Nozzles: 15°, 25°, 40°
- Engine oil 10W-30
- Downstream injector

## LIMITED WARRANTY

All Units 10yr Frame, 5yr Pump, 3yr Engine

## FEATURES

- 1750 RPM slow speed
- CRX®, HONDA®, VANGUARD® key-start engines (battery not included)
- Burner on/off rocker switch and hour meter
- High temperature safety switch
- Isolated pump & engine plate with vibration dampeners
- 3.4 kw generator with two 120V outlets
- 120V burner system
- Wheel brake system
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 horizontal coil
- Large capacity fuel tank



65016



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP	DRIVE	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
DSL4040253E <sup>1</sup>	65016	4000 PSI	4.0 GPM	HONDA® GX390* w/Key-Start	General Pump®	Gear	5.0 gal.	10.0 gal.	540 lbs.
DSL4040333E <sup>1**</sup>	65017	4000 PSI	4.0 GPM	VANGUARD® 479cc* w/Key-Start	COMET	Gear	5.0 gal.	10.0 gal.	540 lbs.
DSL4040132E <sup>1</sup>	65142	4000 PSI	4.0 GPM	CRX® 420* w/Key-Start	COMET	Gear	5.0 gal.	10.0 gal.	540 lbs.
DSL4040232E <sup>1</sup>	65018	4000 PSI	4.0 GPM	HONDA® GX390* w/Key-Start	COMET	Direct	5.0 gal.	10.0 gal.	540 lbs.
DSL4040332E <sup>1**</sup>	65019	4000 PSI	4.0 GPM	VANGUARD® 479cc* w/Key-Start	COMET	Direct	5.0 gal.	10.0 gal.	540 lbs.
DSL4040133E <sup>1</sup>	65131	4000 PSI	4.0 GPM	CRX® 420* w/Key-Start	COMET	Direct	5.0 gal.	10.0 gal.	540 lbs.

## PUMPS

### General Pump® Industrial Triplex

- Thermal relief valve
- Forged brass head
- Heat-resistant ceramic plunger sleeves
- External unloader with bypass hose

### COMET Industrial Triplex Pump

- Thermal relief valve
- Forged brass head
- Heat-resistant ceramic plunger sleeves
- External unloader with bypass hose

## FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance

## HOSE

- 3/8" x 50' steel-braided Armor Hose™

## ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT	FUEL TANK
CRX® 420	679cc	External
HONDA® GX390	389cc	External
VANGUARD® 479cc	570cc	External

## DIMENSIONS

All Units L 33" x W 40" x H 45"

<sup>1</sup> - This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* - Indicates engine is equipped with low oil shutdown technology. Refer to page 32 for additional information.

\*\* - Battery not included.