

# COBALT SERIES - HOT WATER

INDUSTRIAL

Take on the toughest cleaning jobs with the Cobalt series. Built with a robust twin-cylinder engine, it delivers dependable power that gets the job done. When turned on the diesel-fired heating system provides up to a 120°F heat rise, helping tackle even the toughest tasks with ease.

## UNIT INCLUDES

- Hose
- Lance
- Trigger gun
- Nozzles: 15°, 25°, 40°, and soap
- Engine oil 10W-30
- Downstream injector

## LIMITED WARRANTY

**ALL UNITS** 10yr Frame, 5yr Pump, 3yr Engine

## FEATURES

- 1750 RPM slow speed
- V-twin horizontal engine with key-start (battery not included)
- NEMA 4X electrical enclosure with burner on/off rocker switch and hour meter
- Corrosion-resistant stainless-steel coil cover
- Isolated pump & engine plate with vibration dampeners
- Burner fuels: No. 1/No. 2 diesel or kerosene
- 1/2" Schedule 80 horizontal coil



65002



MODEL #	PART #	PRESSURE	FLOW	ENGINE	PUMP   DRIVE	GAS TANK	DIESEL TANK	PRODUCT WEIGHT
DCT3555251EDC1 <sup>1</sup>	65002	3500 PSI	5.5 GPM	HONDA® GX690* w/Key-start	General Pump®   Belt	7.5 gal.	7.5 gal.	670 lbs.
DCT3555151E <sup>1</sup>	65144	3500 PSI	5.5 GPM	CRX® 680* w/Key-start	General Pump®   Belt	7.5 gal.	7.5 gal.	670 lbs.
DCT3555341EDC1 <sup>1</sup>	65297	3500 PSI	5.5 GPM	Vanguard® 23HP* w/Key-start	UDOR®   Belt	7.5 gal.	7.5 gal.	670 lbs.
DCT3555241EDC1 <sup>1</sup>	65298	3500 PSI	5.5 GPM	HONDA® GX690* w/Key-start	UDOR®   Belt	7.5 gal.	7.5 gal.	670 lbs.
DCT3555141EDC1 <sup>1</sup>	65351	3500 PSI	5.5 GPM	CRX® 680* w/Key-start	UDOR®   Belt	7.5 gal.	7.5 gal.	670 lbs.
DCT4055151E <sup>1</sup>	65158	4000 PSI	5.0 GPM	CRX® 680* w/Key-start	General Pump®   Belt	7.5 gal.	7.5 gal.	613 lbs.
DCT4050241EDC1 <sup>1</sup>	65299	4000 PSI	5.0 GPM	HONDA® GX690* w/Key-start	UDOR®   Belt	7.5 gal.	7.5 gal.	670 lbs.
DCT4050341EDC1 <sup>1</sup>	65350	4000 PSI	5.0 GPM	Vanguard® 23HP* w/Key-start	UDOR®   Belt	7.5 gal.	7.5 gal.	670 lbs.
DCT4050141EDC1 <sup>1</sup>	65352	4000 PSI	5.0 GPM	CRX® 680* w/Key-start	UDOR   Belt	7.5 gal.	7.5 gal.	670 lbs.

## PUMPS

### General Pump® Industrial Triplex

- 1750 RPM slow speed
- Thermal relief valve
- Forged brass manifold
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

### UDOR® Industrial Triplex Pump

- Forged brass manifold
- Thermal relief valve
- Ceramic-coated plunger sleeves
- External unloader with bypass hose

## FRAME

- Heavy-duty 1-1/2" round tubular steel design
- Powder-coated for corrosion resistance
- Removable feet for forklift capabilities and alternative mounting options

## HOSE

- 3/8" x 50' steel-braided Armor Hose®

## NOZZLES

- Quick-connect nozzles for a variety of cleaning applications

## ENGINES LOW OIL SHUTDOWN

ENGINE	DISPLACEMENT
CRX® 680	679cc
VANGUARD® 570cc	570cc
HONDA® GX690	688cc

## DIMENSIONS

All Units L 42" x W 40" x H 38"

<sup>1</sup> - This product is 49-State/EPA-Compliant. Not for sale in the state of California.

\* - Indicates engine is equipped with low-oil shutdown technology. Refer to page 34 for additional information.